

Тип масла, заливаемого в редуктор серии ВН

TABELLA 1 – LUBRIFICANTI MINERALI

TABLE 1 - MINERAL LUBRICANTS

TABELLE 1 - MINERALSCHMIERMITTEL

MARCA / MAKE / <i>HERSTELLER</i>	TIPO DI OLIO / TYPE OF OIL / <i>ÖLSORTE</i>
• IP • SHELL • MOBIL • ESSO	MELLANA OIL 220 OMALA OIL 220 MOBILGEAR 630 SPARTAN EP220

TEMPERATURA AMBIENTE / **AMBIENT TEMPERATURE** / *UMGEBUNGSTEMPERATUR* - 5 °C ÷ + 35 °C
TEMPERATURA OPERATIVA / **OPERATING TEMPERATURE** / *BETRIEBSTEMPERATUR* - 5 °C ÷ + 80 °C

TABELLA 2 – LUBRIFICANTI SINTETICI

TABLE 2 - SYNTHETIC LUBRICANTS

TABELLE 2 - SYNTHETISCHE SCHMIERMITTEL

MARCA / MAKE / <i>HERSTELLER</i>	TIPO DI OLIO / TYPE OF OIL / <i>ÖLSORTE</i>
• IP • SHELL • KLÜBER	TELUM OIL 320 TIVELA OIL SC 320 SYNTHESO D 320 EP

TEMPERATURA AMBIENTE / **AMBIENT TEMPERATURE** / *UMGEBUNGSTEMPERATUR* - 30 °C ÷ + 50 °C
TEMPERATURA OPERATIVA / **OPERATING TEMPERATURE** / *BETRIEBSTEMPERATUR* - 40 °C ÷ + 130 °C